

Exterior Sheets

Beauty, security and high resistance

Product Description

Ultracem Exterior Sheets represent our high-performance product with special characteristics that broadly satisfy technical parameters required in higher-demand applications, they have special features such as high thicknesses and water repellent treatments and are supplied with a high level of durability and safety in constructions. This floor substrate system is designed by specialists to be used when building second floors for homes, warehouses and mezzanines.

The system has been tested in order to obtain the best performance in applications that require bonding ceramic and porcelain floors, among others.









Advantages

- They may be cut, sanded, nailed, perforated, and screwed with conventional tools
- They provide isolation from noise and heat
- They accept all types of finishes
- Interior or exterior use
- Water, fire and termite resistant
- Proven savings in installation time
- Clean work with no sand or cement
- Residential and commercial uses

Types

Uses	Thickness	Nominal Size
Roof Base	14mm/17mm	5/8" or 3/4"
Flooring	22mm	1"
Wall Partitions	11mm	1/2"

Joint Treatment Guide

-  1. Clean and remove dust from the joint and the sloped surface
-  2. For each bucket of PlyRock compound-19kg, add 2 kilograms of cement and one liter of water. Homogenize the mix until a soft paste is obtained
-  3. Fully fill the joint between panels. Then, apply a layer of PlyRock filler along the joint by impregnating the edges of the panel.
-  4. Place a Plycem joint mesh along the joint. Secure it on the surface.
-  5. Fully cover the mesh with a layer of PlyRock filler, and let dry for 24 hours.
-  6. Apply two layers of PlyRock filler on the entire surface of the panels. Let dry for 2 hours between layers. Smooth and paint according to architectural requirements.



ULTRACEM

The New Cutting Edge in Constructive Solutions



Impact-Resistant



Lightweight and resistant



Plague-resistant



Water Repellent



Moisture-resistant



Non-combustible



Easy Installation

www.ultracemintl.com

sales@ultracemintl.com